FEATURE OF TECHNICAL SERVIC

Detailed architectural and structural design of civil works with BIM **Subject** return of the Thermoelectric Power Station in Armenia Yerevan 250MW

return of the Thermoelectric Power Station in Armenia Yerevan 250MW Combined Cycle Power Plant (YCCPP2) - Yerevan Capital City

€ 1'400'000,00

Carried out by SGAI S.r.l. di E. Forlani & C.

Client RENCO S.p.a.

Service length 2017 I phase 2018 – on going II phase

Value of works I phase \in 1'800'000,00 II phase \in 4'700'000,00

E.02 € 1'800'000,00 S.05 **Categories value**

S.06 € 700'000,00

THERMOELECTRIC POWER STATION - Design according to BIM methodology

As part of the energy production development program, organized by the Armenian Ministry of Energy (MOE), the construction of a new combined cycle (gas and steam) thermoelectric plant is planned in the suburbs of the city of Yerevan, adjacent to another existing plant.

The project involves the construction of numerous buildings for housing machinery and equipment, as well as service structures, technological systems and access roads to the various sectors of the plant. The entire project was managed and developed by applying the BIM management process, firstly creating the 3D model of the entire plant, containing all the information necessary for its construction, operation and maintenance. In this context, the positions of BIM Manager and BIM coordinator were prepared, carrying out the management, coordination, control and verification of interference (Clash Detection) and information required by the LOD (Level Of Detail). In particular, the detailed structural and architectural design, according to BIM methodology, of the following buildings was carried out: Operation Building, Main Security Building and Electrical Building. In addition, special foundations for gas and steam turbines have been designed, characterized by strong vibrations, as well as the foundations of numerous other buildings and complementary works such as: Turbine Building, Warehouse Building, Cooling Tower, HRSG heat recovery unit, chimney (over 60m high), cisterns, pipe racks, retaining walls, etc.


The design of the internal access roads to the plant and the storage areas was also carried out, as well as the hydraulic regulation of the entire area of the plant including the rainwater disposal grid and related treatment network (drains, manholes, pipes, etc.).

3D-BIM Model of the plant




Clash Detectio

		Pozzetto SP_8	-0.114	2020/4/22 08:16	i x:166.576, y:118.244, z:100.010	Element ID: 1175666	800x800sp150	Composite Part :	/20GUA18-BR401-AC30-2"-PA/81	Cylinder
A.	Pozzetto SP_8	Clash14	-0.114	2020/4/22 08:16	x:166.576, y:118.244, z:100.010	Element ID: 1175666	800x800sp150	Composite Part :	/20GUA18-BR401-AC30-2"-PA/B1	Cylinder
	Pozzetto SP_8	Clash44	-0.038	2020/4/22 08:16	x:166.543, y:118.212, z:98.950	Element ID: 1175666	800x800sp150	Composite Part :	/20GUA18-BR401-AC30-2*-PA/B1	Cylinder
1	Pozzetto SP_8	Clash70	-0.020	2020/4/22 08:16	эс166.490, у:118.230, г:99.116	Element ID: 1175666	800x800sp150	Composite Part :	FLANGE 2 of BRANCH /20GUA18-BR401-AC30-2"-PA/BI	l Group
	Pozzetto SP_8	Clash71	-0.020	2020/4/22 08:16	x:166.490, y:118.230, z:99.116	Element ID: 1175666	800x800sp150	Composite Part :	FLANGE 2 of BRANCH /20GUA18-BR401-AC30-2"-PA/BI	l Group
	Pozzetto SP_8	Clash72	-0.020	2020/4/22 08:16	×:166.490, γ:118.253, z:99.052	Element ID: 1175666	800x800sp150	Composite Part :	FLANGE 1 of BRANCH /20GUA18-BR401-AC30-2*-PA/BI	l Group
		Tubo speci	do di 30on ve	ne			. 79			




Modeling of the hydraulic grid and buildings





Plan view of the BIM Mode



Progress of the construction processing

















DYNAMIC ANALISES - Computational aspects, simulation and checks

The foundations of the thermoelectric turbines were analyzed in detail, conducting dynamic and seismic analyzes with finite element numerical models (2D and 3D), solved with the *PLAXIS*, *SAP2000* and *PROSAP* calculation code (for validation and cross-checking of the results). The modeling, combined with an accurate geological and geotechnical investigation campaign, allowed the accurate assessment of the soil structure interaction, allowing to exclude amplifications due to resonance phenomena. In this way, it was possible to reconstruct the stress-strain state of the subsoil during the operation of the vibrating machines, thus obtaining an estimate of the bearing capacity and settlement of the subsoil subjected to cyclical actions.

THERMOELECTRIC POWER STATION – Specialist Design: issues and their resolution

The project involves the design and construction, according to the BIM methodology, of numerous buildings for housing machinery and equipment, as well as service structures, technological systems and access roads to the various sectors of the plant. In support of the design, an accurate geological, geotechnical and hydrogeological campaign was carried out aimed at the lithostratigraphic characterization of the soils on site, the verification of the bearing capacity and the susceptibility to liquefaction. The greatest design difficulties were encountered in sizing and checking the foundations of the vibrating machines of the Turbine Building. Due to their complexity, the generation turbines require special foundations with reduced settlement and great stability against the stresses caused by cyclical actions, connected to the earthquake and vibrations during the operation of the machinery, in order to function properly.

CIVIL AND INDUSTRIAL STRUCTURES LAYER 2 SUITABLE FILL. COMPACTED at World WATERPROOF PROTECTION LAYER 2 PLAXIS TOTAL DISPLACEMENTS 29-MarMACCHINA VIBRANTE-UN ... 224 S.G.A.I. s.r.I. di E. Forlani & C. Radians Radians Radians Text PLAXIS V DISPLACEMENTS 15-Mar-2D-STEAM TURBINE.rG 751 S.G.A.I. s.r.l. di E. Forlani & C. LAYER 3 -0.001038 -0.001241 -0.003227 -0.000161 -0.000146 -0.000001

